



BATTEN

Linear ceiling fixture equipped with high efficiency LED sources.
Fitted with a quick spring clamp for connection in series.

Typology

Quick opening mechanism for wiring.
Easy to connect in series thanks to the quick spring clamp supplied.
Daisy chain assembly of 36 W model is up to 12 fixtures.

Installation

"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation.
Every package is equipped with both brackets and suspension cables (L = 96 cm).


Material

Polycarbonate body: opal polycarbonate screen equipped with internal fins for flow recovery and emission optimization.

Applications

Supermarkets, car parks, laboratories, warehouses.

BASIC	220-240 Vac	Ra >80		30000 h	IP65	IK08	Free Wire	-25°C +35°C	Risk Group 0
--------------	-------------	--------	--	---------	------	------	-----------	----------------	--------------



Characteristic data

Power	36 W	Beam	110°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	65	Flux	3960 lm	Axis	1280 cd
PF	0,9	Tc	3000 K	Ra	>80	IK	IK08
RG	RG0	Color	Grey				

Dimensional characteristics

L	1200 mm
L1	68 mm
H	56 mm

Lighting and photometric features

Beam opening	110°
Flux	3960 lm
Axis	1280 cd
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	30000 h
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	36 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,9
Number of cycles	100000
Operating temperature	-25°C / +35°C

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Barcode single item	8011905937416
---------------------	---------------