



PRAN-U CORNER PROFILE

Features

Aluminium profile for surface or suspension installation with special brackets and cables.
It houses both IP20 and IP68 strips up to 18 mm in width.
Equipped with a compartment to accommodate cables.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:
18 mm

Installation

Surface.
Equipped with a compartment to pass cables through.

This profile can be suspension mounted by using the steel slides and suspension cable kit that are available with a separate code.
The slides can also act as blocks to join two adjacent profiles.

Material

6063 Aluminium profile with a white PC screen.

Accessories

Every 2 metre bar is complete with 1 set of end caps (with and without holes) and 1 set of mounting clips.

Packaging


Supplied in packages of 5 bars, each one measuring 2 meters complete with screen and accessories.

Spare accessories available with a separate code.

Screens with different beam openings, spot, flood and asymmetrical available to replace the standard screen it is equipped with.

-25°C
+35°C

Dimensional characteristics



| | |
|----|---------|
| L | 2000 mm |
| L1 | 32.8 mm |
| H | 20 mm |

Lighting and photometric features

| | |
|---------|------|
| Mercury | 0 mg |
|---------|------|

Electrical characteristics

| | |
|-----------------------|---------------|
| Operating temperature | -25°C / +35°C |
|-----------------------|---------------|

European Directives

| | |
|---|--|
| 2011/65/EU * RoHS 2015/863 * Amending RoHS | |
|---|--|

Logistics data

| | |
|--------------------------------|---------------|
| Item net weight | 920 gr |
| Barcode single item | 8011905933029 |
| Number of pieces multiple pack | 5 |
| Minimum order quantity | 5 |
| Minimum packaging | 5 / 5 |