



## LESEL DOWNLIGHT

### Typology

LED source with SMD technology and high efficiency chip integrated into a recessed luminaire.

### Features

Soft satin effect polycarbonate anti-glare diffuser.  
Non removable built-in power supply.

### Installation

Complete with springs for easy fastening into false ceilings.  
Connection to the mains with terminal block.

### Material

Thermally conductive body; extremely light and manageable.

**BASIC**

220-240  
Vac

Ra >80




25000 h  
L70B30

IP20 VI  
IP43 VO

Wire

-25°C  
+35°C

Risk  
Group 1




120°



### Characteristic data

Power	8 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	Wire	IP	20	Optical compartment IP	43	Flux	600 lm
Axis	230 cd	PF	0,51	Tc	4000 K	Ra	>80
LED Warranty	G3	RG	RG1				

### Dimensional characteristics



Ø	85 mm
H	30 mm

Cutting hole	70
--------------	----

## Lighting and photometric features

Beam opening	120°
Flux	600 lm
Axis	230 cd
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B30
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	8 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,51
Input current	0.06 A
Weighted energy consumption	8 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Photometry

	4000K	H(m)	D(m)	Emax(lx)		
	Ra80		113°			
	Fixture Power	8W	1	3.03	213	
	Source Flux	600lm	2	6.07	53	
	Fixture Flux	600lm	3	9.10	24	
	Efficacy	75lm/W	4	12.14	13	
843182	Imax=355cd/klm	Imax	213cd	5	15.17	9

EulumDat file on the site

## Other Infotech

Reflector	Yes
-----------	-----

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	75 gr
Barcode single item	8011905843182
Number of pieces multiple pack	6
Barcode multiple pack	8011905788469
Minimum order quantity	6