HyperColor
Ceramic burner

HYPERCOLOR G12 - CERAMIC BURNER

Typology
Discharge lamps.

Features
Product reliability. This is what the entire range of Duralamp discharge lamps has in common.
Used in technical and professional installations where relamping is often difficult, discharge lamps must be lamps you can depend upon.

Notes
The HYPERCOLOR range with ceramic burners: excellent control of colour uniformity, colour rendering and colour stability over time.

90 Vac	Ra >90		UV STOP		15000 h	IP20	G12	-15°C +35°C	A↑G G

Characteristic data

Power	70 W	Dimmable	No	Input	90 Vac	Base	G12
IP	20	Flux	6300 lm	Tc	4200 K	Ra	>90

Dimensional characteristics

ø	30 mm
H	100 mm

Technisches Datenblattsheet · Fiche technique · Ficha de datos · Technical datasheet · Scheda tecnica

Lighting and photometric features

Flux	6300 lm
CCT nominal colour temperature	4200 K
Colour of the light	Natural light
Colour rendering index	>90
Lifespan	15000 h
Mercury	5,7 mg

Electrical characteristics

Rated power	70 W
Input voltage	90 Vac
Frequency	50 Hz
Dimmable	No
Input current	0.98 A
Energy efficiency class	G
Operating temperature	-15°C / +35°C
Operating position	360°

Spectrometry

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 62035:2016 (+A1:2020)

Logistics data

Item net weight	30 gr
Barcode single item	8007753356257
Number of pieces multiple pack	12
Barcode multiple pack	8011905771898

Technisches Datenblattsheet Fiche technique Ficha de datos Technical datasheet Scheda tecnica