



## WIRELESS UNIT WITH DALI INTERFACE

A wireless control module with a DALI interface

It generates a local DALI bus which makes it possible to connect a LED driver directly to a DALI interface.

The module can only be used in a closed system and cannot be connected to an existing DALI network.

The module is wireless controlled using a CASAMBI app for smartphones and tablets using Bluetooth 4.0 technology.

The devices create an adaptive, secure and reliable wireless mesh network that can control a large number of fixtures in a simple and efficient way.

One device can be used to control one appliance/strip only.

220-240  
Vac

IP20

Terminals

### Characteristic data

Power	1.1 W	Input	220-240 Vac	Base	Terminals	IP	20
-------	-------	-------	-------------	------	-----------	----	----

### Dimensional characteristics

L1	37 mm
L2	41 mm
L3	14 mm

### Electrical characteristics

Rated power	1.1 W
Input voltage	220-240 Vac

### European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

### Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-11:2002 (+A1:2020)  
CEI EN 61547:2010

## Logistics data

Item net weight	48 gr
Minimum order quantity	1
Minimum packaging	1 / 1