



SLIMFLUX VINTAGE 60X60 - PRO

Typology

Recessed panel "vintage" style, with integrated non replaceable high efficiency LED source.

Features

"Vintage" recessed panel ideal to maintain existing aesthetics and provide significant energy savings and lower maintenance costs. Versions with high colour rendering, Ra 90 and DALI dimmable versions.

Material

Steel body treated with UV resistant polymers; anti-glare louvre high reflectancy aluminized polycarbonate with 83% efficacy.

Power supply


Integrated light source not replaceable.



Characteristic data

Power	38 W	Beam	100°x80°	Dimmable	DALI	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	43	Flux	3750 lm
PF	0,90	UGR	<16	Tc	4000 K	Ra	>90
LED Warranty	G5h24	RG	RG0				

Dimensional characteristics



L	595 mm
H	43 mm

Cutting hole	580x580
--------------	---------

Lighting and photometric features

Beam opening	100°x80°
Flux	3750 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<16

Electrical characteristics

Rated power	38 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Output voltage	25-42 Vdc
Dimmable	DALI
Power factor (PF)	0,90
Max output current	1000 mA
Weighted energy consumption	38 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	3500 gr
Barcode single item	8011905955540
Number of pieces multiple pack	5
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products