

VALO MINI

Typology

Compact adjustable LED downlight with integrated driver.

Features

Classic spot with 75 mm cut-out and 40° aperture.

Available in warm and natural light versions.

Compact and easy to install.

Tilt Adjustability 30°.

Non removable built-in power supply.

Installation

Complete with springs for easy fastening into false ceilings.

Material

Heat resistant, anti-yellowing plastic body.

BASIC

220-240
Vac

Ra 80




15000 h
L70B30

IP20 VI
IP43 VO

Free Wire

-25°C
+35°C

Risk
Group 0




40°



Characteristic data

Power	7 W	Beam	40°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	43	Flux	620 lm
PF	0.5	Tc	3000 K	Ra	80	LED Warranty	G2
Axis	700 cd	RG	RG0				

Dimensional characteristics



L	90 mm
L1	90 mm
H	40 mm

Cutting hole	75x75
--------------	-------

Lighting and photometric features

Beam opening	40°
Flux	620 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B30
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	7 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0.5
Operating temperature	-25°C / +35°C

Photometry

EuLumDat file on the site

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-2:2012
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Barcode single item	8011905987725
Number of pieces multiple pack	20
Barcode multiple pack	8011905990176