



DALI DRIVER

DURASTRIP DRIVERS DALI

Dimming curve expressed as a function of the load, i.e. inversely proportional to the percentage value of the power supply load.
 If the product is used at full load, the dimming curve is linear from 10 to 100%, if it is used at half load, the dimming possibility is halved, i.e. a dimming on the control side of 50% will produce a real load dimming of 25%.
 It is important to distribute the power evenly over the power supplies in the same area of the installation to achieve consistent dimming levels.

200-260 Vac	DALI	IP67	Free Wire	-20°C +45°C	SELV	UL Type HL	EAC	CCC
CB	EN EC 18	MW MEAN WELL	G5 h24					

Characteristic data

Power	96 W	Dimmable	DALI	Input	200-260 Vac	Base	Free Wire
IP	67	PF	0,9	LED Warranty	G5h24		

Dimensional characteristics

L	199 mm
L1	63 mm
H	35.5 mm

Electrical characteristics

Rated power	96 W
Input voltage	200-260 Vac
Frequency	50 Hz
Output voltage	24 Vdc
Dimmable	DALI
Power factor (PF)	0,9
Input current	4 A
Operating temperature	-20°C / +45°C

Other Infotech

Max Case Temperature	90
----------------------	----

LED Warranty

G5h24	<p>Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.</p>
-------	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-13:2015 (+A1:2018)
CEI EN 61547:2010

Logistics data

Item net weight	850 gr
Barcode single item	8011905975821
Minimum order quantity	1
Minimum packaging	1 / 1