



DOWNLIGHT HM - IP43

Typology

Recessed source in relation to the downlight plane: less glare for pleasant surroundings.

Downlight with opaline lens.

A light yet robust fixture: an essential design that can be used everywhere.

Complete with springs for easy fastening into false ceilings.

Heat resistant, anti-yellowing plastic body.

100-240
Vac

Ra >80



20000 h
L70B20

Free Wire

-25°C
+35°C



Characteristic data

Power	12 W	Beam	100°	Dimmable	No	Input	100-240 Vac
Base	Free Wire	Flux	813 lm	Axis	316 cd	PF	0,90
Tc	4000 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics

ø	125 mm
H	102 mm


Lighting and photometric features

Beam opening	100°
Flux	813 lm
Axis	316 cd
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	20000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	12 W
Input voltage	100-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,90
Input current	0.07 A
Weighted energy consumption	12 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry

	4000K	H(m)	D(m)	Emax(lx)		
	Ra85		104°			
	Fixture Power	11W	1	2.56	316	
	Source Flux	814lm	2	5.12	79	
	Fixture Flux	814lm	3	7.68	35	
	Efficacy	72lm/W	4	10.24	20	
A1396	Imax=388cd/klm	Imax	316cd	5	12.81	13

EulumDat file on the site

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	250 gr
Barcode single item	8011905835583
Minimum order quantity	40

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products