



IP67 PWM SIGNAL REPEATER

Features

Dimming and control systems can be used to improve the ambient aspect: they help creating special, different, soft and always lively atmospheres. Moreover, they have an important function of energy saving: by varying the emission and/or activating/deactivating the system or appliances, they allow optimising the presence of solar lighting. Max current 5A / channel.



Characteristic data

Input	12-36 Vdc	Base	Screws	IP	67	LED Warranty	G5h24
-------	-----------	------	--------	----	----	--------------	-------

Dimensional characteristics

L	181 mm
L1	74 mm
H	38 mm

Electrical characteristics

Input voltage	12-36 Vdc
Output voltage	24 Vdc
Operating temperature	-25°C / +35°C

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61347-1:2016 (+A1:2021)
 CEI EN 61347-2-11:2002 (+A1:2020)
 CEI EN 61547:2010

Logistics data

Item net weight	120 gr
Barcode single item	8011905862718
Minimum order quantity	1
Minimum packaging	1 / 1