



STAGNA S2T L1 IP65 - 25000H

Typology

Waterproof linear ceiling light with G13 connection for 2 TUBOLED.
Complete with 25,000h Tuboled.

Features

Quick opening mechanism for wiring.

Installation

"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation.
Every batten is equipped with brackets.

Material

Polycarbonate body: transparent polycarbonate screen equipped with internal fins for flow recovery and emission optimization.

Applications

Supermarkets, car parks, laboratories, warehouses.

BASIC

220-240
Vac

Ra >80



25000 h
L70B50

IP65

IK07

G13

-25°C
+35°C

Risk
Group 0






Characteristic data

Power	18 W	Dimmable	No	Input	220-240 Vac	Base	G13
IP	65	Flux	1850 lm	PF	0,7	Tc	4000 K
Ra	>80	LED Warranty	G2	IK	IK07	RG	RG0

Dimensional characteristics



L	665 mm
L1	95 mm
H	60 mm

Lighting and photometric features

Flux	1850 lm
CCT nominal colour temperature	4000 K
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B50

Electrical characteristics

Rated power	18 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,7
Operating temperature	-25°C / +35°C

Photometry

EuLumDat file on the site

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	630 gr
Barcode single item	8011905017262
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products