



## SLIMFLUX VINTAGE 30X120 - PRO

### Typology

Recessed panel "vintage" style, with integrated non replaceable high efficiency LED source.

### Features

"Vintage" recessed panel ideal to maintain existing aesthetics and provide significant energy savings and lower maintenance costs. Versions with high colour rendering, Ra 90 and DALI dimmable versions.

### Material

Steel body treated with UV resistant polymers; anti-glare louvre high reflectancy aluminized polycarbonate with 83% efficacy.

### Power supply


Integrated light source not replaceable.



### Characteristic data

Power	38 W	Beam	100°x80°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	43	Flux	4100 lm
PF	0,90	UGR	<16	Tc	4000 K	Ra	>90
LED Warranty	G5h24	RG	RG0				

### Dimensional characteristics



L	1195 mm
H	43 mm

Cutting hole	1180x280
--------------	----------


## Lighting and photometric features

Beam opening	100°x80°
Flux	4100 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<16

## Electrical characteristics

Rated power	38 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Output voltage	25-42 Vdc
Dimmable	No
Power factor (PF)	0,90
Max output current	1000 mA
Weighted energy consumption	38 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Photometry

 <p>51375 I<sub>max</sub>=541cd/klm</p>	4000K	H(m)	D1(m)	D2(m)	E <sub>max</sub> (lx)
	Ra90		94°	85°	
	Fixture Power	38W	1	2.14	1.82 1711
	Source Flux	4100lm	2	4.28	3.64 428
	Fixture Flux	4100lm	3	6.42	5.46 190
	Efficacy	108lm/W	4	8.56	7.28 107
	I <sub>max</sub>	2219cd	5	10.70	9.10 68

EuLumDat file on the site

## Other Infotech

Reflector	Yes
-----------	-----

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	3700 gr
Barcode single item	8011905951375
Number of pieces multiple pack	5
Barcode multiple pack	8011905951696
Minimum order quantity	1