



DURANEONFLEX-Q TOP

Uniform and flexible light

Ready-to-light

DuraNeonFlex is a flexible extruded silicone profile, complete with 120 LEDs per meter strip.

The narrow pitch of the chips and Integrated Circuit technology make DNF a perfect light line, homogenous on all its 10 meters of length.

What's best ... it is ready-to-light!

Typology

Flexible light line with uniform emission in two directions depending on the model. The section of the profile can be rounded or squared.

Both models have a TOP and VERT versions.

Features

Flexible light line with continuous lighting: so flexible you can create curves with a minimum diameter of 20 cm.

TOP flex Version: the light is emitted on the upper side of the light channel.

Anti-glare diffuser function.

Maximum length per single power supply: 10 metres.

Installation

It is attached to the surface with the clips; it can be cut following the cutting marks (5cm).

Fitted with different outputs for power supply.

Installation temperature: 0° ~ 35°C; working temperature: -25° +35°C.

Material

Extremely flexible, impact resistant and weatherproof extruded silicone. Minimum colour shift compared to the colour of the chip.

Usage information

Dimmable 0-100%

DALI - DMX

Analogue and digital domotic control systems

Push Dali with ZKCDAFF controllers

CASAMBI compatible

Packaging

Available to order with minimum quantities to be agreed on with the sales force.

DNF can be supplied at any specific length (max length 10 meters for single power supply, cut every 5 cm) with or without the electrical terminals or in 10 m and 50 m reels without terminals.

Colour of the light

Range of white and pure colours both with 120 LED per meter.


RGB version available on DNF and DNF-Q models.



Characteristic data

Power	90 W	Beam	120°	Dimmable	Yes	Input	24 Vdc
Base	Free Wire	IP	65	Flux	4500 lm	Tc	4000 K
Ra	>80	LED Warranty	G4h24	IK	IK07	RG	RG0

Dimensional characteristics



L	10000 mm
L1	16 mm
H	12 mm

Cutting pitch	50 mm
LED pitch	50 mm

Lighting and photometric features

Beam opening	120°
Nominal flux per mt	450 lm/m
Flux	4500 lm
CCT nominal colour temperature	4000 K
Colour rendering index	>80
Lifespan	36000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	90 W
Input voltage	24 Vdc
Dimmable	Yes
Energy efficiency class	This product contains a light source of energy efficiency class "F"
Operating temperature	-25°C / +35°C
Operating position	360°

Photometry

	4000K	H(m)	D(m)	Emax(lx)	
	Ra80		113°		
Fixture Power	9W	1	3.03	156	
Source Flux	450lm	2	6.06	39	
Fixture Flux	450lm	3	9.08	17	
Efficacy	50lm/W	4	12.11	10	
933975 I _{max} =348cd/klm	I _{max}	156cd	5	15.14	6

EulumDat file on the site

LED Warranty

G4h24	Full Guarantee 4 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Item net weight	1935 gr
Barcode single item	8011905933975
Minimum order quantity	1
Minimum packaging	1 / 1