



DURALUM END CAPS

End caps kit

Each length of Duralum can be terminated with silicone end caps to protect and insulate the conductors at the end of a run.



Characteristic data

Dimmable	No						
----------	----	--	--	--	--	--	--

Electrical characteristics

Dimmable	No
----------	----

Standards and Directives

2011/65/UE * RoHS	EN 60598-2-1 * anno 1997
2012/19/UE * RAEE	EN 61347-1 * anno 2009 (+A1:2011, +A2:2013)
2014/30/UE * Compatibilità Elettromagnetica	EN 61347-2-13 * anno 2007
2014/35/UE * Bassa Tensione	EN 62031 * anno 2009 (+A1:2013)
EN 61547 * anno 2010	EN 62493 * anno 2010
EN 55015 * anno 2014	EN 62776
EN 61000-3-2 * anno 2007 (+A1/+A2:2011)	Gruppo di rischio 0
EN 61000-3-3 * anno 2014	2010/30/EU * Energy Consumption
EN 62471 * anno 2010	874/2012 * Regulation for Energy Labelling
IEC/TR 62471-2:2009 (CEI 34-141:2012)	2009/125/CE * Progettazione Eco Compatibile
EN 62031 * anno 2009 (+A1:2013)	1194/2012 * Progettazione Eco Compatibile
EN 60598-1 * anno 2009	

Logistics data

Item net weight	115 gr
Barcode single item	8011905853143

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products