



DECO LED TECNO VINTAGE MATT GLOBE

Typology

Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

Features

Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

Material

Glass bulb.

Notes

Can be used with TRIAC leading edge dimmers. Dimmers' list on www.duralamp.com.



220-240
Vac

Ra 80



15000 h
L70B50

IP20

E27


-25°C
+35°C



Characteristic data

| | | | | | | | |
|-------|--------|------|------|--------------|--------|-------|-------------|
| Power | 7 W | Beam | 320° | Dimmable | Yes | Input | 220-240 Vac |
| Base | E27 | IP | 20 | Flux | 670 lm | PF | 0,5 |
| Tc | 2200 K | Ra | 80 | LED Warranty | G2 | | |

Dimensional characteristics



| | |
|---|--------|
| Ø | 125 mm |
| H | 176 mm |

Lighting and photometric features

| | |
|---|--------------------|
| Beam opening | 320° |
| Flux | 670 lm |
| CCT nominal colour temperature | 2200 K |
| Colour of the light | Warm light |
| Colour rendering index | 80 |
| Lifespan | 15000 h |
| LED lifespan | L70B50 |
| Trigger time | <0,2 s |
| Heating time up to 60% of full efficiency | Instant Full Light |
| Mercury | 0 mg |

Electrical characteristics

| | |
|------------------------------------|---------------|
| Rated power | 7 W |
| Input voltage | 220-240 Vac |
| Frequency | 50 Hz |
| Dimmable | Yes |
| Power factor (PF) | 0,5 |
| Input current | 0.06 A |
| Weighted energy consumption | 7 kWh/1000h |
| Energy efficiency class | F |
| Number of cycles | 100000 |
| Operating temperature | -25°C / +35°C |
| Equivalence with incandescent lamp | 52 |
| Operating position | 360° |

LED Warranty

| | |
|----|--|
| G2 | Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions. |
|----|--|

European Directives

| | |
|--|--|
| 2009/125/EC * Ecodesign 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC 2014/35/EU * LVD 2015/863 * Amending RoHS 2017/1369 * Regulation for Energy Labelling 2019/2015 * Regulation for Energy Labelling 2019/2020 * Regulation for Ecodesign 2021/340 * Amending Reg. Energy Labelling 2021/341 * Amending Reg. Ecodesign | CEI EN 55015:2020 (+A11:2020) CEI EN 60968:2016 CEI EN 61000-3-2:2019 (+A1:2021) CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022) CEI EN 61547:2010 CEI EN 62031:2021 (+A11:2022) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI EN 62560:2013 (+A1:2017/+A11:2020) CEI 34-141:2014 |
|--|--|

Product standards

Logistics data

| | |
|--------------------------------|---------------|
| Item net weight | 110 gr |
| Barcode single item | 8011905844776 |
| Number of pieces multiple pack | 10 |
| Barcode multiple pack | 8011905790059 |
| Minimum order quantity | 10 |
| Minimum packaging | 10 / 10 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products