



## HYPERCOLOR G8,5 - CERAMIC BURNER

### Typology

Discharge lamps.

### Features

Product reliability. This is what the entire range of Duralamp discharge lamps has in common.

Used in technical and professional installations where relamping is often difficult, discharge lamps must be lamps you can depend upon.

### Notes

The HYPERCOLOR range with ceramic burners: excellent control of colour uniformity, colour rendering and colour stability over time.

90 Vac

Ra >84



15000 h

IP20

G8,5


-15°C  
+35°C



### Characteristic data

Power	35 W	Dimmable	No	Input	90 Vac	Base	G8,5
IP	20	Flux	3400 lm	Tc	3000 K	Ra	>84

### Dimensional characteristics



Ø	14.5 mm
H	85 mm

## Lighting and photometric features

Flux	3400 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>84
Lifespan	15000 h
Mercury	4,8 mg

## Electrical characteristics

Rated power	35 W
Input voltage	90 Vac
Frequency	50 Hz
Dimmable	No
Input current	0.5 A
Energy efficiency class	F
Operating temperature	-15°C / +35°C
Operating position	360°

## European Directives

2009/125/EC * Ecodesign 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC 2014/35/EU * LVD 2015/863 * Amending RoHS 2017/1369 * Regulation for Energy Labelling 2019/2015 * Regulation for Energy Labelling 2019/2020 * Regulation for Ecodesign 2021/340 * Amending Reg. Energy Labelling 2021/341 * Amending Reg. Ecodesign	CEI EN 55015:2020 (+A11:2020) CEI EN 62035:2016 (+A1:2020)
--	---

## Product standards

## Logistics data

Item net weight	10 gr
Barcode single item	8007753356295
Number of pieces multiple pack	12
Barcode multiple pack	8011905771850
Minimum order quantity	12
Minimum packaging	12 / 12