



-15°C  
+35°C

## DECORATIVE SUSPENSION PROFILES: P06H

### Features

Suspension profile.  
Circular diffuser with 360° light emission.  
The essential design of this profile and the 360° beam opening, allows for this profile to be installed anywhere whilst responding to many needs using the same aesthetic element.

**CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:**  
30 mm

**MAXIMUM POWER:**  
42W/m

### Installation

Suspension installation.  
Driver and controller must be positioned remotely to the profile.

### Material

6063 aluminium profile with white polycarbonate screen.

### Accessories

Every 3 metre bar is complete with 3 sets of end caps (without hole) and 3 sets of suspension cables.


### Packaging

Supplied in packaging of 1 bars of 3 meters complete with screen and accessories.  
Spare accessories for additional cutting available with a separate code.

### Notes

Thanks to the possibility of using different strips the profile becomes a fixture that can provide different light temperatures, to be used depending on the activities carried out in that space at different times during the day.

## Dimensional characteristics



L	3000 mm
Ø	60 mm

## Electrical characteristics

Operating temperature	-15°C / +35°C
-----------------------	---------------

## European Directives

2011/65/EU * RoHS 2015/863 * Amending RoHS	
---	--

## Logistics data

Barcode single item	8011905913212
---------------------	---------------

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products