



DURA TL - TRACK LIGHT

Typology

Professional LED projectors for track mounting.

Features

Same shape with 3 different dimensions and power choices to cover all requirements. Can be used with Eurostandard Plus tracks as well as with other brands: Staff, Nordlux, Nordic, Global, etc.

Installation

Mounting on 3 phases electrical tracks; fixtures equipped with a safety lock to fix to the tracks.

Material

Die-cast painted aluminium body; black or white colour.

Power supply


Electronic driver integrated in the fixture body.

Beam

High efficiency Ra>85 LED Chip on Board.
Precision optics with dichroic effect lens.
Adjustable from 0° to -90° on the vertical plane and 350° on the horizontal plane.

Notes


Do not use with dimmer.
TRIAC (200-250V) dimmable version on request.



Characteristic data

Power	15 W	Beam	40°	Dimmable	No	Input	110-240 Vac
Base	Eurostandard	IP	20	Flux	1300 lm	PF	0,94
Tc	4000 K	Ra	85	LED Warranty	G5h24	Axis	1990 cd
RG	RG1	Color	White				

Dimensional characteristics



L	108 mm
Ø	100 mm
H	184 mm

Lighting and photometric features

Beam opening	40°
Flux	1300 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	85
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	15 W
Input voltage	110-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,94
Input current	0.09 A
Weighted energy consumption	15 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	648 gr
Barcode single item	8011905851699
Number of pieces multiple pack	10
Barcode multiple pack	8011905851958
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products