



SLIMFLUX VINTAGE 60X60 - PRO

Typology

Recessed panel "vintage" style, with integrated non replaceable high efficiency LED source.

Features

"Vintage" recessed panel ideal to maintain existing aesthetics and provide significant energy savings and lower maintenance costs. Versions with high colour rendering, Ra 90 and DALI dimmable versions.

Material

Steel body treated with UV resistant polymers; anti-glare louvre high reflectancy aluminized polycarbonate with 83% efficacy.

Power supply


Integrated light source not replaceable.

PRO	220-240 Vac	Ra >90		50000 h L70B50	IP20 VI IP43 VO	Free Wire	-25°C +35°C	Risk Group 0	UGR <16

Characteristic data

Power	38 W	Beam	100°x80°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	43	Flux	3750 lm
PF	0,90	UGR	<16	Tc	4000 K	Ra	>90
LED Warranty	G5h24	RG	RG0				

Dimensional characteristics



L	595 mm
H	43 mm

Cutting hole	580x580
--------------	---------

Lighting and photometric features

Beam opening	100°x80°
Flux	3750 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<16

Electrical characteristics

Rated power	38 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Output voltage	25-42 Vdc
Dimmable	No
Power factor (PF)	0,90
Max output current	1000 mA
Weighted energy consumption	38 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC 2014/35/EU * LVD 2015/863 * Amending RoHS 2017/1369 * Regulation for Energy Labelling 2019/2015 * Regulation for Energy Labelling 2019/2020 * Regulation for Ecodesign 2021/340 * Amending Reg. Energy Labelling 2021/341 * Amending Reg. Ecodesign	CEI EN 55015:2020 (+A11:2020) CEI EN 60598-1:2022 CEI EN 60598-2-2:2012 CEI EN 61000-3-2:2019 (+A1:2021) CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022) CEI EN 61547:2010 CEI EN 62031:2021 (+A11:2022) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI EN 62493:2015 CEI 34-141:2014
--	--

Product standards

Logistics data

Item net weight	3500 gr
Barcode single item	8011905951368
Number of pieces multiple pack	5
Barcode multiple pack	8011905951689
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products