



DURABLE PENDANT FOR GU10

Typology

Pendant luminaire for direct lighting, for replaceable lamp with GU10 socket. Round rosette for ceiling installation.

Features

Minimal, simple design and precise finishing. Available in different size and colours.

Material

Die-cast painted aluminium body.

Beam

Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.

Notes


Cable lenght 1,5 m.



Characteristic data

Input	220-240 Vac	Base	GU10	IP	20	LED Warranty	G3
Color	Black						

Dimensional characteristics



Ø	60 mm
H	150 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Operating temperature	-15°C / +35°C

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	313 gr
Barcode single item	8011905981105
Number of pieces multiple pack	20
Minimum order quantity	1
Minimum packaging	1 / 20