



## DURABLE PENDANT FOR GU10

### Typology

Pendant luminaire for direct lighting, for replaceable lamp with GU10 socket. Round rosette for ceiling installation.

### Features

Minimal, simple design and precise finishing. Available in different size and colours.

### Material

Die-cast painted aluminium body.

### Beam

Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.

### Notes


Cable lenght 1,5 m.



### Characteristic data

Input	220-240 Vac	Base	GU10	IP	20	LED Warranty	G3
Color	Black						

### Dimensional characteristics



Ø	60 mm
H	150 mm

### Electrical characteristics

Input voltage	220-240 Vac
Frequency	50-60 Hz
Operating temperature	-15°C / +35°C

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	313 gr
Barcode single item	8011905981105
Number of pieces multiple pack	20
Minimum order quantity	1
Minimum packaging	1 / 20