



## SLIMFLUX ROUND UP&DOWN SUSPENSION

### Typology

Slim LED panel.

### Features

TONDO TRASLUCIDE SUSPENSION: power supply unit integrated in ceiling rose. Light is diffused from the thin white frame to the methacrylate panel. Fractioned by micro incisions on the panel, light is directed predominantly downwards while 30% of the light is projected upwards to create a striking effect that adds to any classic or modern environment. The power cable is one with the suspension cables, therefore invisible. Adjustable suspension wires: MAX 150 cm. Cable attachment with screw and steel cylinder.

### Material

White painted metal body; frontal methacrylate panel.



PLUS

220-240 Vac

Ra 80

30000 h L70B20

IP20

Free Wire

-25°C  
+40°C

Risk Group 0


FLICKER FREE

G3

### Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Flux	3800 lm	PF	0.95	Tc	3000 K
Ra	80	LED Warranty	G3	RG	RG0	Color	White

## Dimensional characteristics



Ø	593 mm
L1	150 mm
H	19.5 mm

## Lighting and photometric features

Flux	3800 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	30000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0.95
Operating temperature	-25°C / +40°C

## Photometry

EuLumDat file on the site

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-1:2022  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	2600 gr
Barcode single item	8011905984304
Number of pieces multiple pack	5
Barcode multiple pack	8011905985769
Minimum order quantity	1
Minimum packaging	1 / 5