

## PANTH ST

### Typology

LED projector "minimal design" for outdoor and indoor applications.

### Features

It can be connected to motion or twilight sensors.  
Very small dimensions and design that meets the most demanding aesthetic requirements.  
Supplied with an orientable mounting bracket.  
Equipped with a GORE-TEX® valve to compensate for pressure variations due to thermal changes and to prevent the formation of condensation in the fixture.

### Material

Painted die-cast metal body.

### Beam

120°

### Notes

Do not use with dimmer.  
Free wire for professional use (1 m long).



### Characteristic data

Power	200 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	Terminals	IP	65	Flux	16000 lm	PF	0,90
Tc	4000 K	Ra	>80	LED Warranty	G3	Axis	6800 cd
RG	RG1	Color	White				

### Dimensional characteristics



L	388 mm
L1	36 mm
H	288 mm

## Lighting and photometric features

Beam opening	120°
Flux	16000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	20000 h
LED lifespan	L70B30
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	200 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,90
Operating temperature	-25°C / +35°C

## Photometry

EuLumDat file on the site

## Other Infotech

Light source replaceability	Replaceable light source by a professional.
Control gear replaceability	Non-replaceable control gear.



## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-5:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	2977 gr
Barcode single item	8011905976279
Number of pieces multiple pack	5
Minimum order quantity	1
Minimum packaging	1 / 5