



## DR111 - WF

### Typology

LED DR111.

### Features

Reflector Effect: coverage of the light source makes these lamps similar to traditional halogen sources they are intended to replace.

### Material

High reflectance metal reflector.

Base in thermoresistant plastic material.

Lightness is an important feature of this product: ideal for use on any type of ceiling or fitting.

### Applications

Professional directional lighting: ideal for use in shops and in areas where accent lighting is required.

### Usage information

Do not use with dimmer.

**BASIC**

220-240  
Vac

Ra 80




25000 h  
L70B50

IP20

GU10


-25°C  
+35°C



### Characteristic data

Power	11 W	Beam	30°	Dimmable	No	Input	220-240 Vac
Base	GU10	IP	20	Flux	1200 lm	Axis	1850 cd
PF	0,70	Tc	3000 K	Ra	80	LED Warranty	G2

### Dimensional characteristics



Ø	111 mm
H	65 mm

## Lighting and photometric features

Beam opening	30°
Flux	1200 lm
Axis	1850 cd
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

## Electrical characteristics

Rated power	11 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,70
Weighted energy consumption	11 kWh/1000h
Energy efficiency class	F
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	101
Operating position	360°

## Photometry

	3000K	H(m)	D(m)	Emax(lx)		
	Ra80		26°			
	Fixture Power	13W	1	0.45	2086	
	Source Flux	900lm	2	0.91	521	
	Fixture Flux	900lm	3	1.36	232	
	Efficacy	69lm/W	4	1.81	130	
850142	Imax=2317cd/klm	Imax	2086cd	5	2.27	83

EulumDat file on the site

## Other Infotech

Reflector	Yes
-----------	-----

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60968:2016  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62560:2013 (+A1:2017/+A11:2020)  
 CEI 34-141:2014

## Logistics data

Item net weight	118 gr
Barcode single item	8011905850142
Number of pieces multiple pack	10
Barcode multiple pack	8011905851132
Minimum order quantity	5
Minimum packaging	5 / 10