



MARAMA

Typology

LED table lamp, dimmable and cordless.
Elegant and essential design, perfect for both modern and classical settings.
Diffused light directed downwards.

Features

Dimmable version with the possibility of changing the light colour from very warm to natural (1800K-4000K).
Marama is operated by a touch on the top of the diffuser: the touch activates on/off, light intensity and choice of desired colour temperature.

Material

Powder-coated aluminium; frosted polycarbonate screen.

Usage information

Battery: battery life of up to 12 hours at full light output and up to 5 days at the lowest output.
Equipped with large capacity 6600mAh rechargeable lithium battery.
Battery charging time: 5~6 hours.

Accessories

Type-C charging cable supplied (can be used with any cable with Type-C jack; USB C charger not included).
USB Multicharger 8 port charge also available to charge 8 lamps simultaneously.

PLUS

5 Vdc

Ra 90



50000 h
L70B50

IP53

-25°C
+45°C

Risk
Group 0



Characteristic data

Power	2 W	Dimmable	Yes	Input	5 Vdc	IP	53
Flux	100 lm	Tc	1800-4000 K	Ra	90	LED Warranty	G3
RG	RG0	Color	Corten				

Dimensional characteristics



Ø	100 mm
Ø1	120 mm
H	350 mm

Lighting and photometric features

Flux	100 lm
CCT nominal colour temperature	1800-4000 K
Colour of the light	CCT
Colour rendering index	90
Lifespan	50000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	2 W
Input voltage	5 Vdc
Dimmable	Yes
Input current	2 A
Operating temperature	-25°C / +45°C

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-4:2019
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	850 gr
Barcode single item	8011905994143
Number of pieces multiple pack	10
Barcode multiple pack	8011905994167
Minimum order quantity	1
Minimum packaging	1 / 10