



## DECO LED G9

G9 lamps working at mains.

### Features

Direct replacement of G9 halogen lamps.  
Pleasant decorative design, suitable also in fittings where the lamp is visible.  
Extremely small size: suitable for use in very small fittings, suspensions or many arms chandeliers.

### Notes

Do not use with dimmer.



220-240  
Vac

Ra 80




15000 h  
L70B50

IP20

G9

-25°C  
+35°C



### Characteristic data

Power	4 W	Beam	320°	Dimmable	No	Input	220-240 Vac
Base	G9	IP	20	Flux	470 lm	PF	0,5
Tc	2700 K	Ra	80	LED Warranty	G2		

### Dimensional characteristics



Ø	15 mm
H	65 mm
H Tolerance	± 3 mm

## Lighting and photometric features

Beam opening	320°
Flux	470 lm
CCT nominal colour temperature	2700 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Mercury	0 mg

## Electrical characteristics

Rated power	4 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,5
Input current	0.03 A
Weighted energy consumption	4 kWh/1000h
Energy efficiency class	E
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	40
Operating position	360°

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60968:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62560:2013 (+A1:2017/+A11:2020)  
CEI 34-141:2014

## Logistics data

Item net weight	10 gr
Barcode single item	8011905922443
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products