




## LINEARE ERRE7S 360° - DIMMABLE

### Typology

LED linear lamp with 360° light emission, ideal for use in luminaires that are enhanced by this type of source.

With a diameter of 22/29 mm and the same length as linear halogen lamps, it can be installed in most luminaires offering the same kind of warm, uniform light.

Do not use with dimmers.



220-240  
Vac

Ra 80




10000 h  
L70B50

IP20

R7s

-25°C  
+35°C



### Characteristic data

Power	10 W	Beam	360°	Dimmable	Yes	Input	220-240 Vac
Base	R7s	IP	20	Flux	1050 lm	PF	0,84
Tc	2700 K	Ra	80	LED Warranty	G2		

## Dimensional characteristics



L	118 mm
Ø	22 mm

## Lighting and photometric features

Beam opening	360°
Flux	1050 lm
CCT nominal colour temperature	2700 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	10000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	10 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	Yes
Power factor (PF)	0,84
Input current	0.5 A
Weighted energy consumption	10 kWh/1000h
Energy efficiency class	F
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	75

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## Logistics data

Item net weight	54 gr
Barcode single item	8011905846718
Number of pieces multiple pack	10
Barcode multiple pack	8011905846725