



TENDERERA

Typology

Circular shape LED lamp.

Features

The new generation circline has made a leap forward from the aesthetic point of view: Tenderera is a lamp that does not need any fitting.

Material

Body impact-resistant plastic, easy to clean.

Beam

Beam angle: 180° diffuses light evenly, precisely where needed.

Notes

Can be completed with suspension wire, ceiling cap and E27 socket.
Do not use with dimmer.

BASIC

220-240
Vac

Ra >80



20000 h
L70B50

IP20

E27


-25°C
+35°C



Characteristic data

Power	24 W	Beam	180°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	20	Flux	2735 lm	PF	0,99
Tc	4000 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics



Ø	200 mm
H	95 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	180°
Flux	2735 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	20000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	24 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,99
Weighted energy consumption	24 kWh/1000h
Energy efficiency class	E
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	164
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	260 gr
Barcode single item	8011905850470
Number of pieces multiple pack	10
Barcode multiple pack	8011905850487
Minimum order quantity	1
Minimum packaging	1 / 10