

## MINILINI



220-240  
Vac

Ra >90



50000 h  
L70B20

IP65

-25°C  
+35°C

Risk  
Group 1



36°x80°



### Characteristic data

Power	32 W	Beam	36°x80°	Dimmable	Yes	Input	220-240 Vac
IP	65	Flux	1700 lm	Axis	1285 cd	Tc	3000 K
Ra	>90	LED Warranty	G5h24	RG	RG1		

## Dimensional characteristics



L	591 mm
L1	40 mm
H	40 mm

## Lighting and photometric features

Beam opening	36°x80°
Flux	1700 lm
Axis	1285 cd
CCT nominal colour temperature	3000 K
Colour of the light	Natural light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B20

## Electrical characteristics

Rated power	32 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	Yes
Operating temperature	-25°C / +35°C

## Photometry

	3000K	H(m)	D1(m)	D2(m)	E <sub>max</sub> (lx)
	Ra90		79°	38°	
Fixture Power	32W	1	1.65	0.68	1323
Source Flux	1700lm	2	3.29	1.37	331
Fixture Flux	1700lm	3	4.94	2.05	147
Efficacy	53lm/W	4	6.59	2.74	83
967574 I <sub>max</sub> =778cd/klm	I <sub>max</sub>	5	8.23	3.42	53

EuLumDat file on the site

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60598-1:2022  
 CEI EN 60598-2-5:2016  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62493:2015  
 CEI 34-141:2014

## Logistics data

Barcode single item	8011905967574
Minimum order quantity	1