



MINILINI



Characteristic data

Power	32 W	Beam	36°x80°	Dimmable	Yes	Input	220-240 Vac
IP	65	Flux	1700 lm	Tc	3000 K	Ra	>90
LED Warranty	G5h24	Axis	1285 cd	RG	RG1		

Dimensional characteristics



L	591 mm
L1	40 mm
H	40 mm

Lighting and photometric features

Beam opening	36°x80°
Flux	1700 lm
CCT nominal colour temperature	3000 K
Colour of the light	Natural light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B20

Electrical characteristics

Rated power	32 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	Yes
Operating temperature	-25°C / +35°C

Photometry

	3000K	H(m)	D1(m)	D2(m)	E _{max} (lx)
	Ra90	79°	38°		
Fixture Power	32W	1	1.65	0.68	1323
Source Flux	1700lm	2	3.29	1.37	331
Fixture Flux	1700lm	3	4.94	2.05	147
Efficacy	53lm/W	4	6.59	2.74	83
967574 I _{max} =778cd/klm	I _{max}	5	8.23	3.42	53

EulumDat file on the site

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-5:2016
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Barcode single item	8011905967574
Minimum order quantity	1