



WALL DMX DIMMER TOUCH

Typology

Dimmers for DURASTRIP white, for DURASTRIP CTC, DURASTRIP RGB and RGB+white.

Features

External interface in tempered glass with high touch sensibility, immediate response to touch and control precision.


4 zones can be controlled separately or synchronised.

Can be used with ZKCDMX, ZKCDMX-R, ZKCDMXW.

Conforms with protocol DMX512 (1990).

Dimmer's driver included in the box (220-240Vac / 5Vdc).


Easy installation and intuitive use.



Characteristic data

Input	5 Vdc	Base	Screws	LED Warranty	G4h24	Color	White
-------	-------	------	--------	--------------	-------	-------	-------

Dimensional characteristics



L	86 mm
L1	86 mm
H	10 mm

Electrical characteristics

Input voltage	5 Vdc
Frequency	50 Hz
Operating temperature	-25°C / +35°C

LED Warranty

G4h24	Full Guarantee 4 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-11:2002 (+A1:2020)
CEI EN 61547:2010

Logistics data

Item net weight	180 gr
Barcode single item	8011905839635
Minimum order quantity	1
Minimum packaging	1 / 1