

## FLEXIBLE PROFILES: PRAPFLEX

### Features

Flexible extruded PMMA highly resistant profile with a white diffusing cover. Can be used to follow curved lines; minimum curve diameter 43 cm.

### CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

12 mm

### MAXIMUM POWER:

10W/m

### Installation

Surface mounting.  
Attach using the clips provided.

### Material

White PMMA profile.

### Accessories


Installation kit included 5 mt.: 10 steel clips, 5 side caps without hole and 5 side caps with holes for cabling.

Installation kit included 20 mt.: 40 steel clips, 20 side caps without hole and 20 side caps with holes for cabling.

### Packaging

Available in two different lengths: L=5m or L=20m.  
Spare accessories for additional cutting available with a separate code.

## Dimensional characteristics



L	5000 mm
L1	17.5 mm
H	11.34 mm

## European Directives

2011/65/EU \* RoHS  
2015/863 \* Amending RoHS

## Logistics data

Item net weight	760 gr
Barcode single item	8011905844714

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products