



TUBOLED GLASS LL6 50.000 H

Typology

T8 LED tubes with high efficiency and 50,000h lifetime.

Features

Replacing 18W, 36W and 58W T8 tubes: high energy saving.
Immediate switch on, no flickering or buzzes.
Great flux maintenance.
Great light uniformity and distribution.
PF: 0.9.
Efficiency: up to 140 lm/W.

Material

White glass body, plastic caps.

Applications

Laboratories, production areas, garages, service corridors, commercial installations.

Usage information

Do not use with dimmer.
In case fluorescent tubes must be replaced, follow the simple assembly instructions indicated.
See instructions on the website.
Do not use in in-series installations.



Characteristic data

Power	20 W	Beam	300°	Dimmable	No	Input	220-240 Vac
Base	G13	IP	20	Flux	2900 lm	PF	0.9
Tc	6400 K	Ra	>80	LED Warranty	G5h24		

Dimensional characteristics



L	1500 mm
Ø	28 mm


Lighting and photometric features

Beam opening	300°
Flux	2900 lm
CCT nominal colour temperature	6400 K
Colour of the light	Cool light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	20 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0.9
Input current	0.097 A
Weighted energy consumption	20 kWh/1000h
Energy efficiency class	D
Operating temperature	-25°C / +35°C

Photometry

	6000K
	Ra80
	Fixture Power 20W
	Source Flux 2800lm
	Fixture Flux 2800lm
	Efficacy 140lm/W
862299	Imax=172cd/klm
	Imax 480cd

EulumDat file on the site

LED Warranty

G5h24	<p>Full Guarantee</p> <p>5 years</p> <p>(24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.</p>
-------	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60968:2016
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62560:2013 (+A1:2017/+A11:2020)
 CEI 34-141:2014

Logistics data

Item net weight	300 gr
Barcode single item	8011905862299
Number of pieces multiple pack	10
Barcode multiple pack	8011905862305
Minimum order quantity	10
Minimum packaging	10 / 10