


DALI - PUSH DALI DRIVER

**Features**  
Can be used with fittings with replaceable remote driver.  
220÷240 V 50/60 Hz  
Lifetime: 50000 h.



220-240  
Vac


  
DALI

30000 h


IP20

Screws


-25°C  
+35°C




SELV



ENEC 05






Characteristic data

Power	42 W	Dimmable	DALI	Input	220-240 Vac	Base	Screws
IP	20	PF	0,97	LED Warranty	G3		

Dimensional characteristics



L	123 mm
L1	82 mm
H	23 mm

## Lighting and photometric features

Lifespan	30000 h
----------	---------

## Electrical characteristics

Rated power	42 W
Input voltage	220-240 Vac
Output voltage	2-100 Vdc
Dimmable	DALI
Power factor (PF)	0,97
Input current	0.23 A
Operating temperature	-25°C / +35°C

## Other Infotech

Max Case Temperature	90
----------------------	----

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-13:2015 (+A1:2018)  
CEI EN 61547:2010

## Logistics data

Item net weight	240 gr
Barcode single item	8011905935467
Minimum order quantity	1
Minimum packaging	1 / 1