

LINEAR J STANDARD

Typology

Low voltage and mains supply halogen lamps.

Features

Excellent colour rendering, low cost, wide diffusion and easy to use.
In addition to energy classes that reflect the limitations of the technology used that is now totally replaceable by more efficient LED models.

Lamp not for sale on the European market.

230 Vac

Ra 100



2000 h

IP20

R7s-15


-15°C
+35°C

320°

Characteristic data

Power	1000 W	Beam	320°	Dimmable	Yes	Input	230 Vac
Base	R7s-15	IP	20	Flux	19100 lm	Tc	3000 K
Ra	100						

Dimensional characteristics



L	189 mm
Ø	10 mm

Lighting and photometric features

Beam opening	320°
Flux	19100 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	100
Lifespan	2000 h
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	1000 W
Input voltage	230 Vac
Frequency	50 Hz
Dimmable	Yes
Input current	4.34 A
Weighted energy consumption	1000 kWh/1000h
Number of cycles	15000
Operating temperature	-15°C / +35°C
Equivalence with incandescent lamp	1123
Operating position	15°

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60432-2:2001 (+A1:2006/+A2:2012)

Logistics data

Number of pieces multiple pack	25
Barcode multiple pack	8011905707163