



SLIMFLUX SL - BASIC

Typology

Ultra-flat LED fixtures with lateral lighting.

Features

Side heat dissipation.
Immediate switch-on.
Colour rendering: Ra>80.
Remote power supply included.
Do not use with dimmer.
If you want to dim or use the multicurrent power supply dimmer.
Class II fittings.

Installation

Possibilities include: recessed, suspended, ceiling/wall.
Surface mounting & adjustable suspension wire kits are available as accessories.

Material

Painted white aluminium body; anti-yellowing PS screen.

Usage information

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

Emergency

SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.

Notes


Providing greater visual comfort, improved definition of detail and reduction of stress.



Characteristic data

Power	30 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Optical compartment IP	43	Flux	3600 lm	PF	>0,9
Tc	4000 K	Ra	>80	LED Warranty	G2	RG	RG0

Dimensional characteristics



L	595 mm
L1	595 mm
H	7.8 mm

Lighting and photometric features

Flux	3600 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	30 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	>0,9
Operating temperature	-20°C / +45°C


Photometry

	4000K	H(m)	D(m)	Emax(lx)
	Ra80		113°	
Fixture Power	30W	1	3.01	1262
Source Flux	3600lm	2	6.01	316
Fixture Flux	3600lm	3	9.02	140
Efficacy	120lm/W	4	12.02	79
Imax=351cd/klm	Imax	5	15.03	50

EulumDat file on the site

Other Infotech

Flicker Free	Yes
Light source replaceability	Replaceable (LED only) light source by a professional.
Control gear replaceability	Replaceable control gear by a professional.



LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	1970 gr
Barcode single item	8011905001087
Number of pieces multiple pack	5
Minimum order quantity	5
Minimum packaging	5 / 5