



## HDS - HIGH PRESSURE SODIUM - ELLIPTICAL

### Typology


Discharge lamps.

### Features

Product reliability. This is what the entire range of Duralamp discharge lamps has in common. Used in technical and professional installations where relamping is often difficult, discharge lamps must be lamps you can depend upon.

### Notes

The HYPERCOLOR range with ceramic burners: excellent control of colour uniformity, colour rendering and colour stability over time.




90±15 Vac	Ra >20		24000 h	IP20	E27	-15°C +35°C	
-----------	--------	--	---------	------	-----	----------------	--

### Characteristic data

Power	70 W	Dimmable	No	Input	90±15 Vac	Base	E27
IP	20	Flux	6400 lm	Tc	2000 K	Ra	>20

## Dimensional characteristics



Ø	55 mm
H	148 mm

## Lighting and photometric features

Flux	6400 lm
CCT nominal colour temperature	2000 K
Colour rendering index	>20
Lifespan	24000 h
Mercury	8,0 mg
Luminous Flux Maintenance at 2000h	94
Luminous Flux Maintenance at 4000h	90
Luminous Flux Maintenance at 6000h	89
Luminous Flux Maintenance at 8000h	86
Luminous Flux Maintenance at 12000h	84
Luminous Flux Maintenance at 16000h	80
Luminous Flux Maintenance at 20000h	78
Lamp survival factor at 2000h	99
Lamp survival factor at 4000h	99
Lamp survival factor at 6000h	98
Lamp survival factor at 8000h	94
Lamp survival factor at 10000h	93
Lamp survival factor at 12000h	88
Lamp survival factor at 15000h	85
Lamp survival factor at 16000h	84
Lamp survival factor at 20000h	78

## Electrical characteristics

Rated power	70 W
Input voltage	90±15 Vac
Frequency	50 Hz
Dimmable	No
Input current	0.98 A
Weighted energy consumption	70 kWh/1000h
Energy efficiency class	F
Operating temperature	-15°C / +35°C
Operating position	360°

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 62035:2016 (+A1:2020)

## Logistics data

Item net weight	170 gr
Barcode single item	8011905042295
Number of pieces multiple pack	12
Barcode multiple pack	8011905734015
Minimum order quantity	12
Minimum packaging	12 / 12