



## LESELI MINI PRO - DIMMABLE

### Typology

Recessed LED fixtures with built-in driver.

### Features

Adjustable dichroic effect optics.  
Tilt Adjustability 30°.  
Special design of the lens ensures excellent light beam diffusion.  
Compact and easy to install.  
Flicker Free.

### Installation

Complete with springs for easy fastening into false ceilings.

### Material


Extruded powder coated aluminium body.



### Characteristic data

Power	9 W	Beam	36°	Dimmable	Yes	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	23	Flux	575 lm
PF	0.9	Tc	4000 K	Ra	>95	LED Warranty	G5h24
Axis	1410 cd	RG	RG1				

### Dimensional characteristics



Ø	85 mm
H	55 mm

Cutting hole	68
--------------	----

## Lighting and photometric features

Beam opening	36°
Flux	575 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>95
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	9 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	Yes
Power factor (PF)	0.9
Weighted energy consumption	9 kWh/1000h
Operating temperature	-25°C / +35°C

## Photometry

EuLumDat file on the site

## Other Infotech

Flicker Free	Yes
Reflector	Yes

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	182 gr
Barcode single item	8011905987695
Number of pieces multiple pack	20
Barcode multiple pack	8011905989712
Minimum order quantity	1