



## COLOR GLS

### Typology

LED lamp with SMD technology with chip defined on a particular wavelength of the spectrum.

### Features

Classic shapes for immediate retro-fit of incandescent lamps in any decorative applications and festoons.

### Material

Body and bulb in polycarbonate.

### Applications

For indoor or outdoor use inside duly protected fittings or Catenaria.

### Notes

Do not use with dimmer.

**BASIC**

200-240  
Vac



20000 h  
L70B50

IP20

E27


-25°C  
+35°C



## Characteristic data

Power	6 W	Beam	200°	Dimmable	No	Input	200-240 Vac
Base	E27	IP	20	PF	0,51	LED Warranty	G2
Color	Blue						

## Dimensional characteristics



Ø	55 mm
H	107 mm

## Lighting and photometric features

Beam opening	200°
Colour of the light	Blue
Lifespan	20000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

## Electrical characteristics

Rated power	6 W
Input voltage	200-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,51
Input current	0.053 A
Number of cycles	100000
Operating temperature	-25°C / +35°C
Operating position	360°

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60968:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62560:2013 (+A1:2017/+A11:2020)  
CEI 34-141:2014

## Logistics data

Item net weight	60 gr
Barcode single item	8011905843557
Number of pieces multiple pack	25
Barcode multiple pack	8011905788834
Minimum order quantity	25
Minimum packaging	25 / 25

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products