

MULTICURRENT DRIVER

Features

Can be used with fittings with replaceable remote driver.
220÷240 V 50/60 Hz
Lifetime 50000 h.
Available with 100-240V voltage upon request.



220-240
Vac



100000 h

IP20

-20°C
+45°C



SELV



FLICKER
FREE



Characteristic data

| | | | | | | | |
|-------|------|--------------|-------|-------|-------------|----|----|
| Power | 40 W | Dimmable | No | Input | 220-240 Vac | IP | 20 |
| PF | 0.95 | LED Warranty | G5h24 | | | | |

Dimensional characteristics

| | |
|----|--------|
| L | 142 mm |
| L1 | 50 mm |
| H | 30 mm |

Lighting and photometric features

| | |
|----------|----------|
| Lifespan | 100000 h |
|----------|----------|

Electrical characteristics

| | |
|-----------------------|---------------|
| Rated power | 40 W |
| Input voltage | 220-240 Vac |
| Output voltage | 28-42 Vdc |
| Dimmable | No |
| Power factor (PF) | 0.95 |
| Input current | 0.35 A |
| Operating temperature | -20°C / +45°C |

Other Infotech

| | |
|----------------------|-----|
| Flicker Free | Yes |
| Max Case Temperature | 90 |

LED Warranty

| | |
|-------|---|
| G5h24 | Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions. |
|-------|---|

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-13:2015 (+A1:2018)
CEI EN 61547:2010

Logistics data

| | |
|------------------------|---------------|
| Item net weight | 104 gr |
| Barcode single item | 8015466162263 |
| Minimum order quantity | 1 |
| Minimum packaging | 1 / 1 |