



DECO LED HIGH POWER HP2

Typology

Range of high power LED lamps with SMD technology and high efficiency chip.

Features

Flux up to 8600 lumens to replace also discharge lamps.

PF: 0.95~97.

Installation

Suitable for outdoor use inside suitable fixtures.

Material

Heat-resistant plastic body with metal inner coating; opaline anti-glare polycarbonate cover.

Usage information

Do not use with dimmer.

In order to replace discharge lamps with Deco Led High Power: make sure the fitting is suitable for direct feeding from the mains.

Notes

In case of installation in public areas, it is advisable to use overvoltage surge protection.

The HP2 models are designed to withstand voltage peaks up to 6KV.

BASIC

220-240
Vac

Ra >80




25000 h
L70B50

IP20

E40


-25°C
+35°C



Characteristic data

Power	70 W	Beam	200°	Dimmable	No	Input	220-240 Vac
Base	E40	IP	20	Flux	10200 lm	PF	0,97
Tc	4000 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics



Ø	137 mm
H	250 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	200°
Flux	10200 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	70 W
Input voltage	220-240 Vac
Dimmable	No
Power factor (PF)	0,97
Weighted energy consumption	70 kWh/1000h
Energy efficiency class	D
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	537

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	600 gr
Barcode single item	8011905987756
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products