



ZK RECESSABLE RINGS FIXED IP65 - SQUARE

Typology

Recessed orientable ring with interchangeable optional optics for MR16, PAR16 lamps and Module.
Fixed IP65 version.
See also IP20 swivel version.

Features


The same ring declined in two versions to fulfill different installation needs in the same environments.

Installation

Equipped with springs for quick installation.
To be completed with T053 or T010 lampholders.

Material


Painted metal body.



Characteristic data

| | | | | | | | |
|-------|------|--|--|--|--|--|--|
| Color | Grey | | | | | | |
|-------|------|--|--|--|--|--|--|

Dimensional characteristics



| | |
|----|-------|
| L | 90 mm |
| L1 | 90 mm |
| H | 33 mm |

| | |
|--------------|----|
| Cutting hole | 72 |
|--------------|----|

Electrical characteristics

| | |
|-----------------------|---------------|
| Operating temperature | -25°C / +35°C |
|-----------------------|---------------|

European Directives

| | |
|---|--|
| 2011/65/EU * RoHS 2015/863 * Amending RoHS | |
|---|--|

Logistics data

| | |
|--------------------------------|---------------|
| Item net weight | 94 gr |
| Barcode single item | 8011905836870 |
| Number of pieces multiple pack | 10 |
| Barcode multiple pack | 8011905782153 |
| Minimum order quantity | 1 |
| Minimum packaging | 1 / 10 |