


CONSTANT CURRENT DRIVER

Features

Can be used with fittings with replaceable remote driver.
220÷240 V 50/60 Hz
Lifetime 50000 h.



Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Screws
IP	20	PF	0,95	LED Warranty	G5h24		

Dimensional characteristics

L	119 mm
L1	43 mm
H	28 mm

Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Dimmable	No
Power factor (PF)	0,95
Max output current	600 mA
Operating temperature	-25°C / +45°C

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61347-1:2016 (+A1:2021)
 CEI EN 61347-2-13:2015 (+A1:2018)
 CEI EN 61547:2010

Logistics data

Minimum order quantity	1
Minimum packaging	1 / 1