



PLASTER-IN PROFILES: P05A

Features

Anodised aluminium profile for trimmed plaster-in flush recessed installation. Recessed support along the profile for perfect stability.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

10 mm

MAXIMUM POWER:

15W/m

Installation

For recessed installation in plasterboard or ceilings with tiles. Cabling can be in line with the profile or exit the bottom of the profile.

Material

6063 aluminium profile with white polycarbonate screen.

Accessories

Every 1 metre bar is complete with a set of end caps (with and without hole) and a set of mounting clips.


Packaging

Supplied in minimum packages of 5 bars, each one measuring 1 meter complete with screen and accessories.

Spare accessories for additional cutting available with a separate code.

-15°C
+35°C

Dimensional characteristics



L	1000 mm
L1	35.2 mm
H	14.5 mm

Electrical characteristics

Operating temperature	-15°C / +35°C
-----------------------	---------------

European Directives

2011/65/EU * RoHS 2015/863 * Amending RoHS	
---	--

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products