



SLIMFLUX SL UGR - PRO - NO DRIVER

Typology

Ultra-flat LED fixtures with lateral lighting.
Panels of this range are supplied WITHOUT driver: please select the required driver from the range.

Features

Side heat dissipation.
Immediate switch-on.
Colour rendering: Ra>80.
Do not use with dimmer.
If you want to dim or use the multicurrent power supply dimmer.
UGR version.
Class III fittings.

Installation

Installations: suspended, recessed.
No available frames for surface mounting of the 62x62 panel.
Surface mounting & adjustable suspension wire kits are available as accessories.

Material

White painted aluminium body; high transmittance optical PMMA screen.

Usage information

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

Emergency

SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.

Packaging

SL model: 5 pieces pack with single items' box.

Notes

This panel does NOT include the driver: please select the required product from the range.
Providing greater visual comfort, improved definition of detail and reduction of stress.

PRO

220-240 Vac

Ra >80

50000 h L80B20

IP20 VI IP43 VO

Connector

-20°C +45°C

Risk Group 0


UGR <19

FLICKER FREE

Characteristic data

Power	33 W	Dimmable	No	Input	220-240 Vac	Base	Connector
IP	20	Optical compartment IP	43	Flux	4350 lm	UGR	<19
Tc	4000 K	Ra	>80	LED Warranty	G5h24	RG	RG0

Dimensional characteristics



L	615 mm
L1	615 mm
H	9 mm

Lighting and photometric features

Flux	4350 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L80B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<19

Electrical characteristics

Rated power	33 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Operating temperature	-20°C / +45°C

Photometry

EuLumDat file on the site

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	3800 gr
Barcode single item	8011905973933
Number of pieces multiple pack	5
Minimum order quantity	1
Minimum packaging	1 / 5