



SLIMFLUX NWB3 PANELS 60X60 - BASIC

Typology

Ultra-flat LED fixtures with lateral lighting

Features

Side heat dissipation.
Immediate switch-on.
Colour rendering: Ra>80.
Remote power supply included.
Do not use with dimmer.
If you want to dim or use the multicurrent power supply dimmer.
UGR version also available.
Class II fittings.

Installation

Possibilities include: recessed, suspended, ceiling/wall.
Surface mounting & adjustable suspension wire kits are available as accessories.

Material

White painted metal body.
Anti-yellowing PS screen.
LGP (Light Guide Plate) in PS anti-yellowing.

Usage information

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

Emergency


SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.



Characteristic data

Power	40 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	43	Flux	3400 lm
PF	0,90	Tc	3000 K	Ra	>80	LED Warranty	G2
RG	RG0						

Dimensional characteristics



L	595 mm
L1	595 mm
H	10 mm

Lighting and photometric features

Beam opening	120°
Flux	3400 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,90
Weighted energy consumption	40 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 60598-2-2:2012
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Item net weight	2300 gr
Barcode single item	8011905934415
Number of pieces multiple pack	5
Barcode multiple pack	8011905934941
Minimum order quantity	5