



DURABLE WALL LAMP BRICK

Typology

Double emission wall light for replaceable lamp with GU10 socket.

Features

The design of the fixture sees the positioning of the lamp a few centimetres from the wall allowing the cone of light to develop on the wall in a harmonious way, without excessive glare.

Installation

By means of the rear bracket.

Material

Aluminium body with epoxy coating; glass diffusers.

Beam


Can be used with all GU10 lamps in the catalogue: select the desired power and beam opening.



Characteristic data

Input	220-240 Vac	Base	GU10	IP	44	LED Warranty	G3
Color	White						

Dimensional characteristics



L	67 mm
L1	95 mm
H	152 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Operating temperature	-15°C / +35°C

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	520 gr
Barcode single item	8011905980610
Number of pieces multiple pack	20
Minimum order quantity	1
Minimum packaging	1 / 20